

Hydrogenated Pyrolysis Gasoline (Pygas)

Product Specification

CHARACTERISTICS	METHOD	UNIT	TYPICAL	SPECIFICATION	
				Min	Max
API Gravity @ 60% *	ASTM D287		41.6		
Specific Gravity @ 60% *	ASTM D4052/D1298		0.82		
Bromine No.	ASTM D1159	g/100g	<1.0		1.0
Distillation 95%, deg C	ASTM D86/D3710	$^{\circ}$	195		205.0
Sulfur	ASTM D5453/D7041	Wt ppm	0.69		1.0
RVP psia	ASTM D6377	Psia	7.4		
C5 & Lighter	ASTM D6729/30	Wt%	15 - 29		
Benzene	ASTM D6729/31	Wt%	32.0 - 48		
Toluene *	ASTM D6729/32	Wt%	4.5 - 6.0		
Thiopene (2)	ASTM D6228/7011	Wt ppm	0.29		
Color, Saybolt	ASTM D156	Saybolt	29		

^{*} For information only

Technical Disclaimer

Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. SAFFRON Group does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contact, tort or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as any international laws which may be encountered in the use thereof. Such questions should be investigated by the user.