



SAFFRON GROUP

C20-C24 Product Specification

CHARACTERISTICS	METHOD	UNIT	SPECIFICATION	
			Min	Max
<C18	GLC	wt. %	-	0.10
C18	GLC	wt. %	-	3.00
C20	GLC	wt. %	35.0	55.00
C22	GLC	wt. %	25.0	45.00
C24	GLC	wt. %	10.0	26.00
C26	GLC	wt. %	-	2.00
>C26	GLC	wt. %	-	0.10
Water	ASTM E 1064	ppm by wt	-	100
Color	ASTM D 6045	Saybolt	30	-
Appearance	ASTM D 4176	-	Bright and Clear	-
API Gravity @ 60°F *	ASTM D 287	-	-	-
Specific Gravity *@ 60°F/60°F *	ASTM D 287	-	-	-

**Sales Specification*

Technical Disclaimer

Before using this product, the user is advised and cautioned to make its own determination and assessment of the safety and suitability of the product for the specific use in question and is further advised against relying on the information contained herein as it may relate to any specific use or application. It is the ultimate responsibility of the user to ensure that the product is suited and the information is applicable to the user's specific application. SAFFRON Group does not make, and expressly disclaims, all warranties, including warranties of merchantability or fitness for a particular purpose, regardless of whether oral or written, express or implied, or allegedly arising from any usage of any trade or from any course of dealing in connection with the use of information contained herein or the product itself. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself. Further, information contained herein is given without reference to any intellectual property issues, as well as any international laws which may be encountered in the use thereof. Such questions should be investigated by the user.

FOR MORE INFORMATION :

SAFFRON GROUP • Georg-Wilhelm-Str. 181 • D-21107 Hamburg
Fon +49 (0) 40 55435542-0 • Fax +49 (0) 40 55435542-9 • info@saffron-group.com • www.saffron-group.com